



NOTE:  
Dimensions in millimeters  
[inches are in brackets]

**00-97100i Rooflight**  
**00-97110i Rooflight w/ LED**

**00-97000i Rooflight**  
**00-97010i Rooflight w/ LED**

Features

- Manual lift with 4 Open Positions
- Pleated Screen & Shade provides option of full sun, full shade or partial shade/sun combination
- Fits 700mm x 500mm [27.56 x 19.70 inches] Opening
- Optional Passive Ventilation
- White Interior Frame
- Sized for 23mm to 42mm [0.90 to 1.65 inches] Roof Thickness with no cutting required
- Rooflight with LED operates on 12 Volt DC, 2 amp serve
- Rooflight with LED includes a Remote Receiver
- Agency Listings:  
CE Listed, RoHS Compliant  
R43  
RCM

Features

- Manual lift with 4 Open Positions
- Pleated Screen & Shade provides option of full sun, full shade or partial shade/sun
- Fits 700mm x 500mm [27.56 x 19.70 inches] Opening
- Optional Passive Ventilation
- White Interior Frame
- Sized for 42mm to 60mm [1.65 to 2.36 inches] Roof Thickness with no cutting required
- Rooflight with LED operates on 12 Volt DC, 2 amp serve
- Rooflight with LED includes a Remote Receiver
- Agency Listings:  
CE Listed, RoHS Compliant  
R43  
RCM